






Model Number	GR3-AL-TF-112MB3-2-B-D-5.5-230 460-60
MFG PN	T112M1-2
List Price	--

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data				General Data	
Rated Motor Output Power		5.5 HP		Frame Size	112
Rated Motor Speed		3510 r/min		Enclosure	TEFC
Rated Motor Voltage (3 Phase)		230 460-60 Volts - HZ		Approximate Weight	66.22
Rated Motor Current		12.6/6.30 Amps		NEMA Design	A
Service Factor		1.15		IP Rating	55
KVA Code		L		Insulation Class	F
Nominal Efficiency		88.5 %		Tropicalization	YES
Nominal Power Factor		0.9 cosθ		Duty	Cont.
Full Load Torque Ft-Lb		8.03 Ft-Lb		Cable Entry	M25 X 1.5
Temp Rise @ Full Load °C		43		Feet Removable	YES
Efficiency Level		IE3 - NEMA Premium		Double Drilled	NO
Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	
Locked Rotor	-	327	67.55	40	
Breakdown	-	405	-	Rated Altitude (M)	
Pull Up	-	246	-	1000	
125% of FL	3496	-	7.73	Coating	
75% of FL	3540	-	4.87	7024 - Graphite Grey	
50% of FL	3561	-	3.65	Shaft Grounding	
No Load		-	2.12	NO	
Hazardous Location	Class 1, Div 2, Grp A,B,C,D			Brake Voltage (DC)	
				Brake Torque (N-M)	
				Mechanical Data	
				Bearing DE Side	
				6306ZZ	
				Bearing NDE Side	
				6206ZZ	
				Moment of Inertia	
				kg.m2	
				Noise Level	
				Per NEMA dB (A)	
CT VFD Range		--		Loaded Torque Curves	
				--	
P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor					
Certifications	UL	CSA	DOE		
File Numbers	323353	224693	096A		
Wiring Diagram	3PH 9 Lead IEC Dual Voltage				
CONNECTION DIAGRAM 					

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540



MODEL NUMBER	GR-112MB3-AL	ISSUE DATE:	04/2025
DIMENSIONS	in		
CASTING MATERIAL	ALUMINUM	WWW.TECHTOPIND.COM	

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540