



Model Number	GR3-AL-TF-184JP-2-B-D-5-230 460-60
MFG PN	T184T5U2B
List Price	--

All data shown at HIGH voltage setting

Format | STD 3 Phase

Electrical Data		General Data	
Rated Motor Output Power	5 HP	Frame Size	184
Rated Motor Speed	3510 r/min	Enclosure	TEFC
Rated Motor Voltage (3 Phase)	230 460-60 Volts - HZ	Approximate Weight	70.18
Rated Motor Current	11.5/5.77 Amps	NEMA Design	A
Service Factor	1.25	IP Rating	55
KVA Code	L	Insulation Class	F
Nominal Efficiency	88.5 %	Tropicalization	YES
Nominal Power Factor	0.91 cosθ	Duty	Cont.
Full Load Torque Ft-Lb	7.4010784 Ft-Lb	Cable Entry	1.25
Temp Rise @ Full Load °C	34.1	Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium	Double Drilled	NO

Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)
Locked Rotor	-	309	61.29	40
Breakdown	-	410	-	Rated Altitude (M)
Pull Up	-	235	-	1000
125% of FL	3499.2	-	7.1416	Coating
75% of FL	3543.1	-	4.4642	7045 - Graphite Grey
50% of FL	3562.6	-	3.3248	Shaft Grounding
No Load	--	-	2.3	NO

Load Data		Mechanical Data	
Hazardous Location	Class 1, Div 2, Grp A,B,C,D	Bearing DE Side	6306ZZ
		Bearing NDE Side	6306ZZ
		Moment of Inertia	-- kg.m2
		Noise Level	Per NEMA dB (A)

CT VFD Range	--	Loaded Torque Curves	--
P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor			

Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A
Wiring Diagram	3PH 9 Lead Dual Voltage		



