



Model Number GR3-AL-TF-215JM-2-B-D-15-230|460-60

MFG PN T215T15U2B

List Price --

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data

General Data

Rated Motor Output Power	15 HP	Frame Size	215
Rated Motor Speed	3535 r/min	Enclosure	TEFC
Rated Motor Voltage (3 Phase)	230 460-60 Volts - HZ	Approximate Weight	149.6
Rated Motor Current	22.8/11.4 Amps	NEMA Design	A
Service Factor	1.25	IP Rating	55
KVA Code	L	Insulation Class	F
Nominal Efficiency	91.7 %	Tropicalization	YES
Nominal Power Factor	0.9 cosθ	Duty	Cont.
Full Load Torque Ft-Lb	22.0313744 Ft-Lb	Cable Entry	1.25
Temp Rise @ Full Load °C	53	Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium	Double Drilled	NO

Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	357	186.4	Rated Altitude (M)	1000
Breakdown	-	476	-	Coating	7024 - Graphite Grey
Pull Up	-	78	-	Shaft Grounding	Yes
125% of FL	3510.1	-	20.255	Brake Voltage (DC)	--
75% of FL	3548.7	-	12.442	Brake Torque (N-M)	--
50% of FL	3566.3	-	8.9919	Mechanical Data	
No Load	--	-	4.591		

Hazardous Location	Class 1, Div 2, Grp A,B,C,D			Bearing DE Side	6309 C3
				Bearing NDE Side	6309 C3
				Moment of Inertia	-- kg.m2
				Noise Level	Per NEMA dB (A)

CT VFD Range	--	Loaded Torque Curves	--
P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor			

Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A

Wiring Diagram	3PH 12 Lead Dual Voltage
----------------	--------------------------



