




Model Number	GR3-CI-TF-200LB35-4-BR-D-40-230 460-60
MFG PN	T 200L1-4
List Price	--

All data shown at HIGH voltage setting


Format STD 3 Phase

Electrical Data				General Data	
Rated Motor Output Power		40 HP		Frame Size	200
Rated Motor Speed		1780 r/min		Enclosure	TEFC
Rated Motor Voltage (3 Phase)		230 460-60 Volts - HZ		Approximate Weight	585.2
Rated Motor Current		94.2/47.1 Amps		NEMA Design	A
Service Factor		1.15		IP Rating	55
KVA Code		H		Insulation Class	F
Nominal Efficiency		94.1 %		Tropicalization	YES
Nominal Power Factor		0.85 cosθ		Duty	Cont.
Full Load Torque Ft-Lb		0 Ft-Lb		Cable Entry	M40 X 1.5
Temp Rise @ Full Load °C		57.7		Feet Removable	YES
Efficiency Level		IE3 - NEMA Premium		Double Drilled	NO
Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	289	407.3	Rated Altitude (M)	1000
Breakdown	-	236	-	Coating	7024 - Graphite Grey
Pull Up	-	217	-	Shaft Grounding	NO
125% of FL	1775	-	57.82	Brake Voltage (DC)	--
75% of FL	1786	-	36.66	Brake Torque (N-M)	--
50% of FL	1791	-	27.89	Mechanical Data	
No Load	1797	-	18.14	Bearing DE Side	6312 C3
Hazardous Location	Class 1, Div 2, Grp A,B,C,D			Bearing NDE Side	6312 C3
				Moment of Inertia	-- kg.m2
				Noise Level	Per NEMA dB (A)
CT VFD Range		--		Loaded Torque Curves	
				P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor	
Certifications	UL	CSA	DOE		
File Numbers	323353	224693	096A		
Wiring Diagram	3PH 12 Lead IEC Dual Voltage				

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540



FRAME: 200LB35	HP:	RPM:	PHASE: 3	VOLT:	ENCL: TEFC	FREQ: 60 Hz	FLA:	LRA:
----------------	-----	------	----------	-------	------------	-------------	------	------



	MODEL NUMBER:		REV.	BY	DATE	CHANGES
	GR3-CI-TF-200LB35		1			
	MFG PN:		2			
			3			
	MATERIAL: ALUMINUM		4			
	UNITS: INCH	BY: SSEE	5			
	DRAWN: 8/20/2018		6			
WWW.TECHTOP.COM		7				

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540