



Model Number GR3-CI-TF-284JM-2-BR-D-25-230|460-60

MFG PN T284TS25U2B

List Price --

All data shown at HIGH voltage setting

Format STD 1 Phase

Electrical Data		General Data	
Rated Motor Output Power	25 HP	Frame Size	284
Rated Motor Speed	3550 r/min	Enclosure	TEFC
Rated Motor Voltage (1 Phase)	230 460-60 Volts - HZ	Approximate Weight	398
Rated Motor Current	60.06/30.3 Amps	NEMA Design	A
Service Factor	1.25	IP Rating	55
KVA Code	M	Insulation Class	F
Nominal Efficiency	91.7 %	Tropicalization	YES
Nominal Power Factor	85 cosθ	Duty	Cont.
Full Load Torque Ft-Lb	36.43744 Ft-Lb	Cable Entry	1.25
Temp Rise @ Full Load °C	59.3	Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium	Double Drilled	NO

Load Data	RPM	Trq %FL	Current Amps	Mechanical Data	
Locked Rotor	-	207	204.5	Bearing DE Side	6311 C3
Breakdown	-	274	-	Bearing NDE Side	6311 C3
Pull Up	-	120	-	Moment of Inertia	-- kg.m2
125% of FL	3536	-	32.15	Noise Level	Per NEMA dB (A)
75% of FL	3560	-	21.26		
50% of FL	3574	-	15.14		
No Load	3594	-	6.96		

Hazardous Location	Class 1, Div 2, Grp A,B,C,D		Loaded Torque Curves		--
--------------------	-----------------------------	--	----------------------	--	----

CT VFD Range	--	P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor			
--------------	----	---	--	--	--

Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A

Wiring Diagram 3PH 12 Lead Dual Voltage



