



Model Number GX3-AL-TF-284TC-6-B-D-15-230|460-60

MFG PN T284T15U6B

List Price --



All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data				General Data	
Rated Motor Output Power	15 HP			Frame Size	284
Rated Motor Speed	1180 r/min			Enclosure	TEFC
Rated Motor Voltage (3 Phase)	230 460-60 Volts - HZ			Approximate Weight	260.92
Rated Motor Current	38.2/19.1 Amps			NEMA Design	A
Service Factor	1.25			IP Rating	55
KVA Code	K			Insulation Class	F
Nominal Efficiency	91.7 %			Tropicalization	YES
Nominal Power Factor	0.79 cosθ			Duty	Cont.
Full Load Torque Ft-Lb	67.1216 Ft-Lb			Cable Entry	1.25
Temp Rise @ Full Load °C	41.9			Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium			Double Drilled	NO
Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	238	170.5	Rated Altitude (M)	1000
Breakdown	-	333	-	Coating	7024 - Graphite Grey
Pull Up	-	123	-	Shaft Grounding	Yes
125% of FL	1180	-	21.37	Brake Voltage (DC)	--
75% of FL	1188	-	15.25	Brake Torque (N-M)	--
50% of FL	1192	-	12.14	Mechanical Data	
No Load	1196	-	9	Bearing DE Side	6311 C3
Hazardous Location	Class 1, Div 2, Grp A,B,C,D			Bearing NDE Side	6311 C3
				Moment of Inertia	-- kg.m2
				Noise Level	Per NEMA dB (A)

CT VFD Range		--	Loaded Torque Curves	--
			P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor	

Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A
Wiring Diagram	3PH 12 Lead Dual Voltage		



FRAME: 280TC | HP: | RPM: | PHASE: 3 | VOLT: 208-230/460V | ENCL: TEFC | FREQ: 60 Hz | FLA: | LRA:

