



Model Number	GX3-AL-TF-286TC-4-B-D-30-230 460-60
MFG PN	T286T30U4B
List Price	--



All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data				General Data	
Rated Motor Output Power	30 HP			Frame Size	286
Rated Motor Speed	1770 r/min			Enclosure	TEFC
Rated Motor Voltage (3 Phase)	230 460-60 Volts - HZ			Approximate Weight	330.44
Rated Motor Current	67.8/33.9 Amps			NEMA Design	A
Service Factor	1.25			IP Rating	55
KVA Code	K			Insulation Class	F
Nominal Efficiency	93.6 %			Tropicalization	YES
Nominal Power Factor	0.87 cosθ			Duty	Cont.
Full Load Torque Ft-Lb	88.95456 Ft-Lb			Cable Entry	1.25
Temp Rise @ Full Load °C	59.6			Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium			Double Drilled	NO
Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	298	329.5	Rated Altitude (M)	1000
Breakdown	-	364	-	Coating	7024 - Graphite Grey
Pull Up	-	214	-	Shaft Grounding	Yes
125% of FL	1769	-	42.62	Brake Voltage (DC)	--
75% of FL	1782	-	27.52	Brake Torque (N-M)	--
50% of FL	1788	-	21.25	Mechanical Data	
No Load	--	-	14.41	Bearing DE Side	6311 C3
Hazardous Location	Class 1, Div 2, Grp A,B,C,D			Bearing NDE Side	6311 C3
				Moment of Inertia	-- kg.m2
				Noise Level	Per NEMA dB (A)

CT VFD Range	--	Loaded Torque Curves	--
P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor			


Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A
Wiring Diagram	3PH 12 Lead Dual Voltage		





Model Number	GX3-AL-TF-286TC-4-B-D-30-230 460-60
MFG PN	T286T30U4B
List Price	--
Base Frame	GX-286TC-AL-TF

FRAME: 280TC | HP: | RPM: | PHASE: 3 | VOLT: 208-230/460V | ENCL: TEFC | FREQ: 60 Hz | FLA: | LRA:



MODEL NUMBER:
GX3-AL-TF-280TC
MFG PN:

REV	BY	DATE
1		
2		
3		
4		
5		
6		
7		

CHANGES

MATERIAL: ALUMINUM
UNITS: INCH BY: SSEE
DRAWN: 7/31/2019
WWW.TECHTOP.COM

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540