



Model Number GX3-CI-TF-449T-6-RR-E-300-460-60

MFG PN T449T300U6B

List Price --

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data				General Data	
Rated Motor Output Power	300 HP			Frame Size	449
Rated Motor Speed	1185 r/min			Enclosure	TEFC
Rated Motor Voltage (3 Phase)	460-60 Volts - HZ			Approximate Weight	3238
Rated Motor Current	351 Amps			NEMA Design	A
Service Factor	1.15			IP Rating	55
KVA Code	G			Insulation Class	F
Nominal Efficiency	95.8 %			Tropicalization	YES
Nominal Power Factor	0.84 cosθ			Duty	cont
Full Load Torque Ft-Lb	1316 Ft-Lb			Cable Entry	1.25
Temp Rise @ Full Load °C	79			Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium			Double Drilled	NO
Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	231	2392	Rated Altitude (M)	1000
Breakdown	-	313	-	Coating	7024 - Graphite Grey
Pull Up	-	16	-	Shaft Grounding	YES
125% of FL	1187	-	430	Brake Voltage (DC)	--
75% of FL	1193	-	272	Brake Torque (N-M)	--
50% of FL	1195	-	207	Mechanical Data	
No Load	--	-	--	Bearing DE Side	NU319
Hazardous Location	Class 1, Div 2 Grp A,B,C,D			Bearing NDE Side	6319 C3
				Moment of Inertia	-- kg.m2
				Noise Level	Per NEMA dB (A)
CT VFD Range		--		Loaded Torque Curves	
				P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor	
Certifications	UL	CSA	DOE		
File Numbers	323353	224693	096A		
Wiring Diagram	3Phase 6 Lead				



Model Number	GX3-CI-TF-449T-6-RR-E-300-460-60
MFG PN	T449T300U6B
List Price	--
Base Frame	GX-449T-CI-TF

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540