



Model Number

SD3-184TC-2-BR-E-5-460-60

MFG PN

T184T5U2B

List Price

--

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data

General Data

Rated Motor Output Power	5 HP	Frame Size	184
Rated Motor Speed	3510 r/min	Enclosure	TEFC
Rated Motor Voltage (3 Phase)	460-60 Volts - HZ	Approximate Weight	99.88
Rated Motor Current	5.7 Amps	NEMA Design	B
Service Factor	1.25	IP Rating	56
KVA Code	J	Insulation Class	F
Nominal Efficiency	88.5 %	Tropicalization	YES
Nominal Power Factor	0.92 cosθ	Duty	Cont.
Full Load Torque Ft-Lb	10.15 Ft-Lb	Cable Entry	1.25
Temp Rise @ Full Load °C	34.1	Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium	Double Drilled	NO

Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	178	8.3	Rated Altitude (M)	1000
Breakdown	-	268	-	Coating	7024 - Graphite Grey
Pull Up	-	137	-	Shaft Grounding	YES
125% of FL	3480	-	7.2	Brake Voltage (DC)	--
75% of FL	3534	-	4.32	Brake Torque (N-M)	--
50% of FL	3.1	-	--	Mechanical Data	
No Load	3597	-	1.53	Bearing DE Side	6306ZZ

Hazardous Location	CL1 Div2 Grp A,B,C,D	Moment of Inertia	-- kg.m2
		Noise Level	Per NEMA dB (A)
		Loaded Torque Curves	
		--	

CT VFD Range

--

P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor

Certifications	UL	CSA	DOE
----------------	----	-----	-----

File Numbers	323353	224693	096A
--------------	--------	--------	------

Wiring Diagram	3PH Single Voltage SD3
----------------	------------------------



